

# Performance of a Wind Turbine Blade in Sandstorms Using a CFD-BEM Based Neural Network

Iham F. Zidane<sup>1, 2\*</sup>, Greg Swadener<sup>2</sup>, Xianghong Ma<sup>2</sup>, Mohamed F. Shehadeh<sup>3</sup>, Mahmoud H. Salem<sup>1</sup>, Khalid M. Saqr<sup>1</sup>

[1] Mechanical Engineering Department, College of Engineering and Technology, Arab Academy of Science, Technology and Maritime Transport (AASTMT), 1029 Abu Kir, Alexandria – Egypt

[2] School of Engineering and Applied Science, Aston University, Aston Triangle, Birmingham, B4 7ET, U.K

[3] Marine Engineering Department, College of Engineering and Technology, Arab Academy of Science, Technology and Maritime Transport (AASTMT), 1029 Abu Kir, Alexandria – Egypt

\*Corresponding Authors: Greg Swadener Email: [J.G.SWADENER@aston.ac.uk](mailto:J.G.SWADENER@aston.ac.uk)  
Iham F. Zidane Email: [iham\\_zidane@aast.edu](mailto:iham_zidane@aast.edu)

## Abstract

In arid regions, such as the North African desert, sandstorms impose considerable restrictions on horizontal axis wind turbines (HAWT) which have not been thoroughly investigated. This paper examines the effects of debris flow on the power generation of HAWT. Computational Fluid Dynamics (CFD) models were established and validated to provide novel insights on the effects of debris on the aerodynamic characteristics of NACA 63415. To account for the change in chord length and Reynolds number along the span of the blade and the 3D flow patterns, the power curves for a wind turbine were obtained using the Blade Element Momentum (BEM) method. We present a novel coupled application of neural network, CFD and BEM to investigate the erosion rates of the blade due to different sandstorm conditions. The proposed model can be scaled and developed to assist in monitoring and prediction of HAWT blade conditions. This work shows that HAWT performance can be significantly diminished due to the aerodynamic losses under sandstorm conditions. The power generated under debris flow conditions can decrease from 10 to 30 % compared to clean conditions.

**Keywords:** wind energy; wind turbine blade aerodynamics; debris flow; surface roughness; CFD-BEM model; neural network

## Nomenclature

$a$	Axial Induction Factor (-)
$\hat{a}$	Tangential Induction Factor (-)
$AOA$	Angle of Attack ( $^{\circ}$ )
$b$	Number of Blades (-)
$c$	Airfoil Chord Length (m)
$C_d$	Drag Coefficient (-)
$C_l$	Lift Coefficient (-)
$C_m$	Torque Coefficient (-)
$C_n$	Normal Load Coefficient (-)
$C_p$	Power Coefficient (-)
$C_t$	Tangential Load Coefficient (-)
$D_p$	Particle Drag Force Coefficient (-)
$d_p$	Sand Particle Diameter (m)
$dF_D$	Element Drag (N)
$dF_L$	Element Lift (N)
$dF_N$	Element Normal (N)
$dF_T$	Element Tangential (N)
$dM$	Torque (Nm)
$dT$	Thrust Force (N)
$m_x$	Additional Particle Acceleration ( $m/s^2$ )
$P$	Rotor Shaft Power (watt)
$r$	Local Radius (m)
$Re$	Reynolds Number (-)
$Re_p$	Relative Reynolds Number for the Sand Particle (-)
$Re_{\lambda}$	Microscale Reynolds Number (-)
$R_{erosion}$	Particle erosion ( $g/m^2$ )
$V_0$	Real Value of Velocity (m/s)
$V_p$	Particle Velocity (m/s)
$V_{rel}$	Relative Velocity (m/s)
$Y^+$	Dimensionless Wall Distance (-)
$\alpha$	Characteristic Ratio Between the Sand and Air (-)
$\mu$	Fluid Dynamic Viscosity ( $kg/m\ s$ )
$\rho$	Fluid Density ( $kg/m^3$ )
$\rho_p$	Sand Particle Density ( $kg/m^3$ )
$\Phi$	Relative Wind Angle ( $^{\circ}$ )
$\omega$	Rotational Speed (rad/s)

## 1.0 Introduction

In aeronautics, the determination of airfoil performance is vitally important. Computational Fluid Dynamics (CFD) and Blade Element Momentum (BEM) approaches are the leading methods used to simulate wind turbine blade performance. The BEM method analyses the flow field and blade aerodynamics, to calculate the rotor shaft torque and maximize the power generated[1-5]. BEM is fast with low computational cost, and implementation is relatively simple. However, CFD is more accurate and provides more detailed results, but incurs higher computational cost [5]. The CFD-BEM mixed approach was used in designing HAWT blades and predicting the wind turbine performance [5]. For example, Esfahanian et al. [6] determined the aerodynamic coefficients of span wise 2D sections of NREL Phase II wind turbine blades using CFD and then use BEM to predict the turbine performance. The CFD-BEM mixed approach had a much lower computational costs than the CFD-only approach yet a high degree of accuracy was obtained, which was verified using experimental results. Yang et al. [7] used a 2D CFD simulation to derive the lift and drag coefficients. The extracted airfoil data were input directly into a BEM code, which was firstly compared with experimental data for the axial and tangential forces on the blade. Then, they used these derived airfoil data sets to determine the axial and tangential forces for different blade pitch and wind velocity. Good agreement was obtained compared to experiments. On the other hand, the CFD-BEM model has also been used for other applications such as tidal stream turbines [8] and marine current turbines [9].

Research concerning the performance and deficit in energy yield of horizontal axis wind turbines (HAWT) for locations subject to dust and sand abrasion is still incomplete, while arid regions are a key focus for further development of large scale wind farms [10-12]. Akour et al. [13] used BEM theory for the blade design of airfoils BW3, A18 and SG6043. To account for changes in the blade chord length along the span and 3D flow patterns, the power coefficients of each blade was obtained using the software package QBlade. The simulation results were validated using a prototype tested in open air environment. Also, Darbandi et al. [14] obtained the blade aerodynamics coefficients using

1 CFD simulation after validating against experimental data for a 1 megawatt wind turbine airfoil. The  
2 CFD results proved that the blade roughness could effectively reduce the aerodynamic coefficients of  
3 a clean airfoil. BEM theory was used to predict the performance of the 1-megawatt wind turbine blade.  
4 Results showed that due to the rough surface the 1-megawatt wind turbine could be faced with 25%  
5 reductions in its annual energy production. In addition, Pechlivanoglou et al. [15] studied the  
6 aerodynamic effects of various types of roughness-related shape deviations on wind turbines using  
7 XFOil investigations. The XFOil simulation results were validated using wind tunnel measurements.  
8 Measurements of power produced by wind turbines operated in sandy conditions were also used to  
9 determine the actual effects of rough surfaces. Power predictions made using the state BEM method  
10 were correlated with the actual power measured.

11 Artificial neural network (ANN) algorithm was used for wing sections and airfoils performance  
12 optimization in various research studies. Important contributions are made by ANN in the airfoil  
13 designs and the tip speed ratio (TSR) selection. For instance, Chen and Agarwal[16] proposed a genetic  
14 algorithm with an ANN to optimize the wind turbines' flatback airfoils. The technique was proved to  
15 find the optimal flatback airfoils. A neuro-fuzzy inference system was introduced by Ata and Kocyigit  
16 [17] in application of wind turbine in order to estimate its TSR and power factor. Proposed neuro-  
17 fuzzy inference system was shown by the model that it improves the conventional methods  
18 performance. Yurdusev et al. [18] investigated the optimum TSR of the wind turbine airfoil designs  
19 hugely used in practice as well. A demonstration of a multi-layer feed-forward neural network-based  
20 model was done. The ANN proposed model's results proved that it is fast and accurate. It showed that  
21 the algorithm can be modified into other airfoil designs easily due to the neural networks'  
22 generalization and adaptable capabilities. In Mortazavi et al. [19] , the airfoil design for the blade  
23 sections of HAWT were done. They used computational fluids dynamics to train their ANN algorithm  
24 in order to obtain a Pareto optimal set of solutions for the airfoil section's geometrical characteristics.  
25 Some studies in literature applied ANN for fault classification were carried out in the past decades,

1 where the monitored component could be discovered by the method whether it is faulty or not.  
2 Saravanan and Ramachandran[20] for instance, developed an ANN with a high potential in monitoring  
3 the fault conditions of the gear box. Moreover, a multi-layer back propagation neural network-based  
4 model was used by Momoh and Button[21] for detecting any Direct Current arcing faults in a  
5 spacecraft used by NASA in its experimental set up. The operator can only know if the component  
6 was failed or not using that way. Fault development or estimation cannot be tracked by the Operator.  
7 On the other hand, the methodology to automatically predict early faults of wind turbine main bearings  
8 was shown by Zhang [22] . This is done by analyzing SCADA data based on ANN.

9 The main aim of the current study is to analyze HAWT performance and the energy yield  
10 deficit due to debris flow using CFD-BEM modelling. Also, a new technique is proposed using ANN  
11 to predict the amount of erosion occurred at different debris flow conditions. The results will provide  
12 wind turbine designers with a method to estimate the performance of wind turbines installed in dusty  
13 environments and its change over time.

## 14 **2.0 CFD-BEM Model**

15 The 3D wind turbine performance is predicted using QBlade software, because its results have  
16 been verified by several researchers by comparison with wind tunnel test data and results from full  
17 scale wind turbines [23]. QBlade software uses a BEM code that is based on an algorithm developed  
18 by Hansen [24].

19 In the presented study, QBlade software was used to compute the aerodynamics of a wind  
20 turbine made of three blades of 20.5 meters in length. Figure 1 presents the layout of the wind turbine  
21 blade and the airfoil used which is NACA 63415. Individual data sets for clean and rough conditions  
22 due to debris flow were prepared according to the results obtained by CFD. These results represent the  
23 lift and drag coefficients of the chosen airfoil over an angle of attack range from 0° to 10°.

1 The basic assumptions used follow from the assumptions of the BEM theory, which is  
2 summarized as:

- 3 • The blade is discretized into segments.
- 4 • Any aerodynamic interaction between segments is neglected.
- 5 • Lift and drag forces on the blades are determined using the airfoil characteristics.
- 6 • The wind turbine performance is determined by the BEM method using the Qblade  
7 software Package.
- 8 • While the aerodynamic interaction is neglected in determining the lift and drag coefficients,  
9 Qblade makes a Glauert correction for the aerodynamic effects of the neighboring elements.

10 In the current study, a control approach, maximum power point tracking (MPPT), is used to  
11 determine the optimal tip speed ratio (TSR) to use in the operation of the stall-regulated system [5].

## 12 **2.1 CFD Model Description and Simulation Details:**

14 Reynolds-averaged Navier-Stokes (RANS) equations were used to simulate two-dimensional,  
15 viscous, incompressible flow. The continuity equation and momentum equation based on RANS  
16 equations are:

$$17 \frac{\partial u_i}{\partial x_i} = 0 \quad (1)$$

$$18 \frac{\partial}{\partial t}(\rho u_i) + \frac{\partial}{\partial x_j}(\rho u_i u_j) = \frac{\partial p}{\partial x_i} + \frac{\partial}{\partial x_j} \left[ \mu \left( \frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right) - \overline{\rho u_i' u_j'} - \alpha \rho_p \frac{\partial V_{pi}}{\partial t} \right] \quad (2)$$

19 where  $\alpha$  is the sand to air characteristic ratio,  $\rho_p$  is the particle density and  $V_p$  is the particle velocity.

20 CFD simulations for clean air flow conditions were run for comparison with wind tunnel  
21 experimental data taken from [25] to verify the numerical model for the free-stream flow over the  
22 NACA 63415 airfoil. The experiments were conducted at a Reynolds number of  $1.6 \times 10^6$ .

23 A comparison between the numerical results at Reynolds numbers of  $1.6 \times 10^6$ ,  $460 \times 10^3$  and  
24  $300 \times 10^3$  and the experimental data of the lift ( $C_l$ ) and drag ( $C_d$ ) coefficients variation with the angle  
25 of attacks (AOA) have been investigated using different turbulence models. This is shown in figure 2.

1 As shown in figures in figure 2 (a) and (b), the numerical results of SST k- $\omega$  model had good  
2 agreement with the experimental data at Reynolds number  $1.6 \times 10^6$ , except for small deviations in the  
3 lift coefficient. On the other hand, in figure 2 (c), (d), (e) and (f), the transition SST model gave the  
4 closest match with the expected data at Reynolds numbers of  $460 \times 10^3$  and  $300 \times 10^3$ . Since separated  
5 flow is directly connected to flow in the boundary layer, the transition SST turbulence model should  
6 best capture this critical phenomena for wind turbine applications [26]. Similar results have been found  
7 for other airfoils typically used with wind turbines, such as S822 [28].

8 As shown in figure 2 (e) and (f), using the transition SST turbulence model, the drag coefficient  
9 values along the angle of attack variation at Reynolds number  $300 \times 10^3$  are much higher compared to  
10 the reference experimental data. However, the lift coefficient has lower values along the variation of  
11 the angle of attack. This is due to the transitional separation bubble phenomenon. According to the  
12 study presented by [27] for NACA 63415 airfoil, a transitional separation bubble occurs when the flow  
13 over the airfoil experiences decreasing pressure causing it to separate from the surface. After the flow  
14 separates, a detached shear layer form. A transition to turbulent flow occurs within the unstable shear  
15 layer. In the turbulent flow, momentum transfer is enhanced, which leads to reattachment. The size of  
16 the transitional separation bubble increases with decreasing Reynolds number. The boundary layer  
17 forms over the top of the separation bubble and therefore the airfoil drag increases substantially. The  
18 transitional separation bubble and thickening of the boundary layer also affects the airfoil lift.

19 As presented in the authors' previous study in reference [29], the grid contained 120,878 nodes,  
20 and the height of the grid next to the airfoil surface was  $7 \times 10^{-6}$  m. The dimensionless wall distance  
21  $Y^+$  values were less than 1 over the entire airfoil surface.

22 After validating the 2D CFD simulation model at the three Reynolds number values with the  
23 experimental results from [25] in clean air, the Discrete Phase Model was utilized to predict the effect  
24 of sand particles concentration and angle of attack on the erosion rate of the blade. The sand particle  
25 diameter ( $d_p$ ) for this study was selected as  $250 \mu\text{m}$  with a sand density of  $2500 \text{ kg/m}^3$  based on studies

1 in the Arabian Peninsula and Southern Africa [30, 31]. Three mass flow rate values were studied  
 2 during the CFD simulation. These values are 100 kg/s, 200 kg/s and 400 kg/s. Each mass flow value  
 3 is equivalent to a certain value of the characteristic ratio ( $\alpha$ ) between sand and air flow.

4 The Discrete Phase Model represents the sand particles in the continuous phase using round  
 5 particles. The trajectories, heat transfer and mass transfer of these discrete phase entities are computed  
 6 and simulated. Full coupling between the phases is included. The trajectory of the sand particle is  
 7 predicted by integrating the force balance on the particle. This force balance is presented in a  
 8 Lagrangian reference frame. The balance of the forces acting on the particle and the particle inertia,  
 9 can be presented as:

$$11 \frac{dV_p}{dt} = [D_p(V_{rel} - V_p)] + \left[ \frac{g_x(\rho_p - \rho)}{\rho_p} \right] + m_x \quad (3)$$

$$12 D_p = \frac{18 \mu C_d Re_p}{\rho_p d_p^2 24} \quad (4)$$

13  
 14 where,  $D_p (V_{rel} - V_p)$  is the drag force per unit particle mass,  $m_x$  is the virtual mass flow which is  
 15 neglected since the density ratio between air to sand is very small,  $V_{rel}$  is the fluid velocity relative to  
 16 the airfoil,  $\mu$  is the fluid dynamic viscosity coefficient,  $\rho$  is the air density,  $\rho_p$  is the density of the sand  
 17 particle,  $d_p$  is the sand particle diameter,  $Re_p$  is the relative Reynolds number for the sand particle [32].

18  
 19 The characteristic ratio ( $\alpha$ ) between sand and air flow is

$$20 \alpha = \frac{\text{Volumetric Flow Rate of Sand}}{\text{Volumetric Flow Rate of Air}} \quad (5)$$

21 The erosion rate from particle impact is calculated for wall surfaces. The erosion rate is  
 22 calculated as:

$$23 R_{Erosion} = \sum_{p=1}^{N_{Particles}} \frac{\dot{m}_p C(d_p) f(\theta) v^{b(v)}}{A_{face}} \quad (6)$$

24 Where  $\dot{m}_p$  is the mass flow rate of the injected discrete particles,  $C(d_p)$  is a function of sand  
 25 particle diameter,  $\theta$  is the impact angle of the particle path with the wall face,  $f(\theta)$  is a factor



1 which is a function of impact angle,  $v$  is the relative particle velocity,  $b(v)$  is a function of relative  
2 particle velocity, and  $A_{face}$  is the area of the cell face at the wall. Default values are  $C= 1.8 \times 10^{-9}$ ,  
3  $f=1$ , and  $b=0$  [32-34].  $C$ ,  $f$  and  $b$  values for sand eroding are given by Edwards et al.[35].

4 According to Lain and Sommerfeld [36], a multiphase flow simulation could be investigated  
5 using one-way coupling in sand/air flow cases with a characteristic ratio ( $\alpha$ ) up to  $6.3 \times 10^{-4}$ . Lain and  
6 Sommerfeld [36] found a good agreement between the turbulence modelling strategies used and the  
7 experimental measurements by Tsuji et al. [37] in the multi-phase flow. Accordingly, the values of the  
8 characteristic ratio ( $\alpha$ ) for each Reynolds number were chosen up to  $6.3 \times 10^{-4}$ . Tables 1, 2 and 3  
9 represent the equivalent values of the characteristic ratio ( $\alpha$ ) for the three values of the mass flow rate  
10 at each Reynolds number used in the CFD simulation.

11 Bose et al. [38], Monchaux and Dejoan [39] and Malloupas et al. [40] showed that two-way  
12 coupling makes some difference to the results even for  $\alpha$  in the range of  $10^{-5}$  to  $10^{-4}$  if  $Re_\lambda < 50$ , where  
13  $Re_\lambda$  is the Reynolds number based on the Taylor microscale length. However, Mora et al. [41] found  
14 that two-way coupling has some effect on dissipation and settling time for the fluid droplets in their  
15 study with  $Re_\lambda$  up to 400 or 500. For the flow conditions in the current study,  $Re_\lambda$  is in the range 3000  
16 - 18000. Therefore, for  $Re_\lambda$  in the range used in the current study, one-way coupling should be  
17 adequate. Further discussion on simulation of small droplets can be found in [42-43].

18 Mass flow rate 400 kg/s could not be simulated at Reynolds number of  $300 \times 10^3$  as the value  
19 of the characteristic ratio ( $\alpha$ ) in that case is higher than  $6.3 \times 10^{-4}$ , which is beyond the range verified  
20 according to [36]. A high characteristic ratio would need a 4-way coupling model to include the particle  
21 effects on turbulence and particle-particle interactions.

## 22 **2.2 Blade Element Momentum Model [24]**

23 BEM theory balances the axial force and moment generated on the rotor blades with changes  
24 in, respectively, the linear and angular momentum of the mass of air flowing through the rotor disc.  
25 This equilibration considers the flow segmented through annular elements of width  $dr$  as shown in  
26

1 figure 3. In the represented BEM model, it was assumed there was no radial dependency and the force  
 2 from the blades on the flow within each annular element is uniform [24] . The data were adjusted to  
 3 360° polars based on the algorithms of Montgomerie and corrected for the tip losses (Prandtl's Loss  
 4 Factor correction). [15,44]. The elements near the root of the blade have angles of attack of greater  
 5 than 10 deg., so there is some loss of accuracy in extrapolating from the CFD data set. However, this  
 6 region accounts for only 15% of the power generated and has minimal erosion, so the overall accuracy  
 7 is only slightly affected.

8 The loads normal to the blade radius acting on the blade are shown in Figure 3. Also shown in  
 9 Fig. 3 are the angle of wind relative to the airfoil ( $\Phi$ ), the angle of attack ( $AOA$ ), the axial and tangential  
 10 induction factors ( $a$ ) and ( $\hat{a}$ ) that significantly affect the real value of the velocity ( $V_0$ ), and the element  
 11 normal (thrust) ( $dF_N$ ) and element tangential ( $dF_T$ ) forces which are generated by element lift ( $dF_l$ ) and  
 12 drag ( $dF_d$ ) forces.

### 13 2.2.1 Forces acting on each blade element:

$$15 \quad dF_N = \frac{1}{2} \rho V_{rel}^2 c C_n dr \quad (7)$$

$$16 \quad dF_T = \frac{1}{2} \rho V_{rel}^2 c C_t dr \quad (8)$$

17 Where,  $\rho$  is the air density,  $V_{rel}$  is the relative velocity,  $c$  is the chord length,  $C_l$  is the lift coefficient  
 18 and  $C_d$  is the drag coefficient,

$$19 \quad C_n = C_l \cos \Phi + C_d \sin \Phi \quad (9)$$

20 and

$$21 \quad C_t = C_l \sin \Phi - C_d \cos \Phi \quad (10)$$

22 From figure 3 it is readily seen from the geometry that:

$$23 \quad V_{rel} \sin \Phi = V_0(1 - a) \quad (11)$$

24 and

$$25 \quad V_{rel} \cos \Phi = \omega r(1 + \hat{a}) \quad (12)$$

1 Where,  $\omega$  is the rotational speed and  $r$  is the local radius.

2 The Thrust force ( $dT$ ) and the torque ( $dM$ ) on the control volume of thickness  $dr$  are:

3 
$$dT = b dF_N dr \quad (13)$$

4 
$$dM = b dF_T r dr \quad (14)$$

5 Where,  $b$  is the number of wind turbine blades.

6 Using equation (11) for  $F_N$  and equation (15) for  $V_{rel}$ , equation (17) becomes:

7  
8 
$$dT = \frac{1}{2} \rho b \frac{V_0^2(1-a)^2}{\sin^2 \theta} c C_n dr \quad (15)$$

9 Similarly, if equation (12) is used for  $F_T$  and equations (15) and (16) are used for  $V_{rel}$ , equation (18)

10 becomes:

11 
$$dM = \frac{1}{2} \rho b \frac{V_0(1-a)\omega r(1+a)}{\sin \theta \cos \theta} c C_t r dr \quad (16)$$

12  
13 **2.2.2 Rate of change of momentum:**

14 Conservation of linear momentum is

15 
$$dT = 4V_0^2 \rho \pi r a(1-a) dr \quad (17)$$

16 However, conservation of angular momentum is

17 
$$dM = 4V_0 \rho \pi \omega r^3 \dot{a}(1-a) dr \quad (18)$$

18  
19 Applying conservation of linear and angular momentum on a blade element of width  $dr$ , the  
20 thrust force and moment supplied by a blade sector can be calculated from Equations (17) and (18).  
21 The solution that simultaneously meets Equations (17), (18), (19) and (20) is found by iterating  
22 respectively the axial and tangential induction factors ( $a$ ) and ( $\dot{a}$ ). The total moment applied at the  
23 rotor shaft is found by summing the partial moments,  $dM$ , of each element of width  $dr$ .

24 
$$P = \int \omega dM \quad (19)$$

25 By summing over the elements, the power at the rotor shaft ( $P$ ) can determined using equation (19).

### 3.0 Erosion Prediction of NACA 63415 Using Neural Network

Using the back-propagation ANN, the total amount of erosion occurred per unit length for the HAWT blade made of NACA 63415 was estimated. Debris flow rate, Reynolds number and the angle of attack are the operating conditions (input data). In MATLAB software version R2015a, the proposed ANN was applied. Input, output and one or more hidden layers are there [45,46]. It was stated in Hertz et al. [47] and Goh's [48] work that the three layers ANN give credible results in most of the study cases. This statement was assured by the literature where ANNs were applied in process control. The three layered ANN was used in almost all of these cases[47,49-52]. Therefore, this proposed ANN consists of three-layer network, where it has in the hidden layer a sigmoid transfer function and in the output layer a linear transfer function.

The sigmoid transfer function  $g(h)$  is

$$g(h) = \frac{1}{1+e^{-\beta h}} \quad (20)$$

Where,  $\beta$  is the rate constant. Three neurons form the input layer, only a single neuron forms the output layer and eight neurons are found in the hidden layer. Trial and error reveal the optimum number of hidden neurons. The implemented ANN in MATLAB software is shown in Figure 4 (a).

In a matrix, a set of input data were organized as columns. Into a second matrix, another set of target data (the correct output for each of the input data) were arranged. From the CFD study mentioned and discussed in the earlier section, these data were obtained. In table 4, the patterns used in the ANN training progress are shown. From the ANN training progress, eight patterns were excluded. However, later on these patterns were used in the developed ANN to test its reliability. The excluded patterns are presented in Table 5. The patterns used in the ANN training progress were normalized because the sigmoid function's computed output can only be between 0 and 1.

Three sets were used where the ANN training progress were divided upon them randomly. The ratios were 85 % used for ANN training, 10 % used for ANN validation and the last 5 % used as a

1 completely independent test of network generalization. The ANN outputs with respect to targets (the  
2 correct CFD output for each of the input data) are shown in figure 4 (b) for training, validation, and  
3 test sets. The data should fall along 45-degree line for a perfect fit, which means that the targets are  
4 equal to the ANN outputs.

## 5 **4.0 Results and Discussion**

### 6 **4.1 Effects of Debris Flow on Lift Coefficient ( $C_l$ ) and Drag Coefficient ( $C_d$ )**

7 After the 2D CFD model was validated using experimental results for clean air flow, the  
8 Discrete Phase Model was used to study the airfoil performance in different debris flow conditions.  
9 The discrete phase particles were set to come out from the inlet with Reynolds number values of  $1.6 \times$   
10  $10^6$ ,  $460 \times 10^3$  and  $300 \times 10^3$ .

11 As shown in figure 5 (a), (b) and (c), the lift coefficient value increases with an increase in  
12 angle of attack due to the rise of the pressure difference between the high- and low-pressure sides for  
13 both clean and rough conditions. As the amount of debris flow rate increases by increasing the debris  
14 mass flow rate, the pressure coefficient difference between low- and high-pressure sides decreases as  
15 the momentum transfer between the Lagrangian and Eulerian increased.

16 On the other hand, as shown in figure 5 (d), (e) and (f), the drag coefficient increases with angle  
17 of attack, for both clean and rough conditions. As the angle of attack increases the drag coefficient  
18 increases more in rough conditions due to debris than in clean conditions. The inclusion of sand  
19 particles in the flow leads to a larger skin frictional drag and thus to larger total drag. The significant  
20 increase in the drag coefficient, combined with a decrease in lift, leads to a severe reduction of the  
21 aerodynamic performance of the airfoil.

22

### 23 **4.2 Effects of Debris Flow concentration and Angle of Attacks on the Erosion Rate of the Blade** 24 **for NACA 63415**

1 This section discusses the sand particles effect on the blade and the rate of erosion caused  
2 during the 3-month annually. For Instance, in Egypt Khamasin sandstorm usually occurs between  
3 March and May, carrying great quantities of sand and dust from the south into the north Africa [11].  
4 The erosion rate variation with the chord length location( $x/c$ ) was studied at angles of attack of  $2^\circ$  and  
5  $10^\circ$ . The erosion near the trailing edge at Reynolds numbers of  $1.6 \times 10^6$ ,  $460 \times 10^3$  and  $300 \times 10^3$  is  
6 understood by following the particle trajectory presented in figure 6. This figure show that at higher  
7 AOA values, the area of direct contact between pressure side and mean flow increases, which in turn  
8 increases the contact with sand particles. However, for smaller AOA values, the sand particles do not  
9 come in contact with the trailing edge.

10 Figures from 7 show the erosion rate for a 3-months period of the suction side at angle of  
11 attacks  $2^\circ$  and  $10^\circ$  at the three Reynolds number values. As shown in the figure, as the Reynolds  
12 number value increases, the amount of erosion through the wind turbine airfoil increase. In addition,  
13 the leading edge of the suction side is the most sensitive part where erosion is maximized. The erosion  
14 rate could reach up to  $0.6 \text{ kg/m}^2$  and  $0.23 \text{ kg/m}^2$  in the high sandstorms concentration at Reynolds  
15 number values of  $1.6 \times 10^6$  and  $460 \times 10^3$  respectively. However, in the case of low sand storms  
16 concentration, erosion rate could be  $0.07 \text{ kg/m}^2$ ,  $0.06 \text{ kg/m}^2$  and  $0.04 \text{ kg/m}^2$  at Reynolds number values  
17 of  $1.6 \times 10^6$ ,  $460 \times 10^3$  and  $300 \times 10^3$  respectively.

18 It is observed that the erosion extends more towards the trailing edge at lower values of the  
19 Reynolds number and lower angles of attack. For Example, the erosion reached the chord length  
20 location( $x/c$ ) at 0.04 m at Reynolds number of  $1.6 \times 10^6$  and angle of attacks  $2^\circ$ . While, by decreasing  
21 the Reynolds number value to  $300 \times 10^3$ , the erosion extended to the chord length location( $x/c$ ) of 0.14  
22 m at the same angle of attack value. On the other hand, at angle of attack  $2^\circ$ , the erosion almost reached  
23 the chord length location( $x/c$ ) at 0.04 m, 0.11 m and 0.14 m at Reynold number values of  $1.6 \times 10^6$ ,  
24  $460 \times 10^3$  and  $300 \times 10^3$  respectively. while, at angle of attack  $10^\circ$ , the erosion was very limited. This

1 means that the suction side is less affected by the erosion caused due to the sand particles at the higher  
2 angle of attack.

3 In contrast, figures from 8 to 13 represent the erosion rate of the pressure side at angle of attacks  
4  $2^\circ$  and  $10^\circ$ . It is observed that, the erosion rate is maximized at higher angle of attacks. At angle of  
5 attack  $10^\circ$ , the maximum erosion rate was almost  $0.46 \text{ kg/m}^2$  and  $0.3 \text{ kg/m}^2$  at Reynolds number values  
6 of  $1.6 \times 10^6$  and  $460 \times 10^3$  respectively in the high sandstorm concentration. While, in case of low  
7 sandstorm concentration, the maximum erosion rate at the same angle of attack value was  $0.08 \text{ kg/m}^2$ ,  
8  $0.04 \text{ kg/m}^2$  and  $0.06 \text{ kg/m}^2$  at Reynolds number values of  $1.6 \times 10^6$ ,  $460 \times 10^3$  and  $300 \times 10^3$   
9 respectively.

10 Compared to the suction side, the pressure side has an opposite eroding behavior with the  
11 change of the angle of attack values. As the angle of attack increases, the pressure side is more affected  
12 by the erosion caused due to the impact of sand particles. As shown in the figures, the erosion was  
13 diffused all over the pressure side chord at AOA  $10^\circ$  especially at Reynolds number values of  $460 \times$   
14  $10^3$  and  $300 \times 10^3$ . Thus, this diffusion is significant at low Reynolds number values.

15

16

### 17 **4.3 Power Curve Output Using BEM Model**

18 The performance of the blade is directly related to its power coefficient ( $C_p$ ). Therefore, to  
19 select an airfoil, the power coefficient of each blade should be found at the operational Reynolds  
20 number.

21 Figure 14 (a) shows the  $C_p$  of the wind turbine rotor versus the tip speed ratio (TSR) in the  
22 clean and rough conditions due to debris flow. A maximum  $C_p$  of approximately 0.38 occurs at TSR  
23 of 9. Note that, because of the extrapolation used in the BEM model, the accuracy decreases with  
24 decreasing TSR. For  $\text{TSR} < 7$ , the data should be regarded as qualitative. For the clean condition case,  
25 the wind turbine rotor can work very well for a TSR from 7.5 to 9.5 since the wind turbine blade nearly

1 maintains the required  $C_p$  value. However, as the debris mass flow rate increases, the maximum  $C_p$   
2 value obtained decreases. For the case of low debris flow, the maximum  $C_p$  value obtained is 0.34,  
3 which shows a 11% decrease when compared to clean operation condition. In addition, the maximum  
4  $C_p$  value obtained, for the case of high debris flow, is almost 0.28. This is a 26% decrease when  
5 compared to the clean operation condition. Figure 14 (b) presents the simulated torque coefficient ( $C_m$ )  
6 produced for the clean rotor surface as well as rough surfaces for various sand/air volumetric ratios.  
7 The maximum torque coefficient produced when wind turbine rotor operates in the clean condition is  
8 0.05. This value could be decreased into 0.037 in case of high debris flow.

9 Figure 14 (c) shows the simulated power curves for the clean rotor surface as well as rough  
10 surfaces for various sand/air volumetric ratios. This power output was optimized by changing the tip  
11 speed ratio value to obtain the optimum value of Torque produced as presented in figure 14 (b).  
12 According to figure 14 (c) and the results of this investigation, surface roughness caused by debris can  
13 results in a high-energy yield deficit. For the case studied, the decrease in power is predicted to be 10%  
14 for low debris flow but could reach 30% for high debris flow compared to clean air.

15

#### 16 **4.4 Nordtank NTK 500/41 Wind Turbine Case Study**

17 Large-scale Wind turbines (LSWT) with a rated power of 50kW-1 MW are a mature  
18 technology and should experience rapid growth in coming decades [5]. Nordtank NTK 500/41 is an  
19 example of a large-scale commercial wind turbine which produces a rated power of 500 kW. This wind  
20 turbine was installed in 1992 for testing and its performance was investigated extensively during 1992-  
21 1999 [53]. The NTK 500/41 is a stall regulated (fixed pitch) turbine with fixed rotational speed control  
22 strategy. Table 6 shows the main parameters of Nordtank NTK 500/41 [53].

23 Using QBlade software and the above rotor simulation curves, the wind turbine power curve  
24 produced by the Nordtank NTK 500/41 wind turbine was simulated for wind speeds 4-25 m/s. The  
25 mechanical power available from the blades shown in Fig. 14 (c) was used by the QBlade simulation



1 for operating the wind turbine at its optimal tip speed ratio for maximum electrical power generation.  
2 When the electrical generation load is applied, the blades will rotate at a slower speed than the stall  
3 limited rotational speed, and the electrical power output will therefore be reduced compared to the  
4 mechanical power from the blades shown in Fig. 14 (c). Figure 14 (d) presents Nordtank NTK 500/41  
5 power curve at different wind speeds in clean and rough conditions. The power curve is oscillating at  
6 the end of it due to small errors in the iterative calculation, which are magnified in the power output  
7 for high wind speeds. Under sandstorm conditions, the power losses from debris flow seen in Figure  
8 14 (d) would directly affect the turbine power. For the current case study, the maximum power loss is  
9 almost 8 %, 14 % and 22 % in low, medium and high debris flow concentrations, respectively.

10

#### 11 **4.5 Neural Network Erosion Per Unit Area Prediction**

12 After the training process of the proposed ANN has been done, the eight excluded patterns  
13 were used to test the reliability of this developed ANN. The ANN and CFD outputs were compared  
14 and the absolute percentage error (APE) for each pattern was calculated. Figure 15 (a) shows a  
15 comparison between the CFD and ANN output for the total erosion on chord per unit area for each  
16 pattern used in the reliability test for the developed neural network. Figure 15 (b) APE between the  
17 CFD and ANN output for the total erosion on chord per unit area for each pattern used in the reliability  
18 test for the developed neural network. As seen in the figure, the average APE is 9.42 %, the maximum  
19 APE is 14.58 % and the minimum APE is 4.33 %. Figure 15 (c) shows the APE between the CFD and  
20 ANN output for the total erosion on chord per unit area for all the patterns used in the ANN training  
21 progress and the reliability test. It has also been listed in the last column in table 4. According to [54],  
22 the average APE is used to evaluate the approximation performance precision of the ANN models.  
23 The average APE of this constructed metamodel is 4.91 %. This value is normally considered  
24 acceptable, and should be given particular consideration since, according to the literature survey, this  
25 is the first ANN model which could estimate the HAWT rate of erosion. Increasing the patterns of the

1 input and output data in the training process helps to maximize the approximation accuracy of this  
2 neural network model. However, this increased training will increase the computational cost and  
3 potentially reduce the applicability of the model to other new scenarios.

## 4 **5.0 Conclusion**

5 In this work, the effect of debris/air flow on the aerodynamic performance of horizontal axis  
6 wind turbines (HAWT) was investigated using CFD-BEM modelling. Before evaluating the rotor  
7 performance using BEM theory, lift and drag coefficients were obtained as a function of angle of attack  
8 through 2D CFD simulations. The CFD simulation results were validated using experimental data in  
9 the clean condition. Then the lift and drag coefficient values during debris flow simulations were  
10 obtained from CFD and used in the BEM theory. Large-scale Wind turbines case study was presented.  
11 Power curves for the wind turbine rotor were obtained and estimated in different debris flow values.  
12 Results based on the BEM method showed that the power generated under sandstorm conditions can  
13 decrease 30% compared to normal conditions. An artificial neural network has been proposed to  
14 predict the total amount of erosion occurred per unit area as a function of the operating conditions of  
15 the wind turbine blade, which are: the debris flow rate, the Reynolds number and the angle of attack.  
16 Therefore, researchers working on wind turbine design, optimization, diagnosis and maintenance  
17 should be aware of the debris flow issues.

18

## 19 **ACKNOWLEDGMENT**

20 The authors acknowledge the support of the Arab Academy for Science, Technology and Maritime  
21 Transport.

22

## 23 **Data Availability**

24 The data that supports the findings of this study are available within the article.

## 1 References

- 2 1. Lanzafame, R. and M. Messina, *Fluid dynamics wind turbine design: Critical analysis,*  
3 *optimization and application of BEM theory.* Renewable Energy, 2007. **32**(14): p. 2291-2305.
- 4 2. Lanzafame, R. and M. Messina, *BEM Theory: How to Take into Account the Radial Flow*  
5 *inside of a 1-D Numerical Code.* Renewable Energy, 2012. **39**(1): p. 440-446.
- 6 3. Bavanish, B. and K. Thyagarajan, *Optimization of Power Coefficient on a Horizontal Axis*  
7 *Wind Turbine Using BEM Theory.* Renewable and Sustainable Energy Reviews, 2013. **26**: p.  
8 169-182.
- 9 4. Ghadirian, A., M. Dehghan, and F. Torabi, *Considering Induction Factor using BEM Method*  
10 *in Wind Farm Layout Optimization.* Journal of Wind Engineering and Industrial  
11 Aerodynamics, 2014. **129**: p. 31-39.
- 12 5. Bai, C.-J. and W.-C. Wang, *Review of Computational and Experimental Approaches to*  
13 *Analysis of Aerodynamic Performance in Horizontal-Axis Wind Turbines (HAWTs).*  
14 Renewable and Sustainable Energy Reviews, 2016. **63**: p. 506-519.
- 15 6. Esfahanian, V., A. Salavati Pour, I. Harsini, A. Haghani, R. Pasandeh, A. Shahbazi, and G.  
16 Ahmadi, *Numerical Analysis of Flow Field Around NREL Phase II Wind Turbine by a*  
17 *Hybrid CFD/BEM Method.* Journal of Wind Engineering and Industrial Aerodynamics, 2013.  
18 **120**: p. 29-36.
- 19 7. Yang, H., W. Shen, H. Xu, Z. Hong, and C. Liu, *Prediction of the Wind Turbine Performance*  
20 *by Using BEM with Airfoil Data Extracted from CFD.* Renewable Energy, 2014. **70**: p. 107-  
21 115.
- 22 8. [Shehata, A.S., Saqr, K.M., Xiao, Q., Shehadeh, M.F., Day, A. Performance analysis of wells](#)  
23 [turbine blades using the entropy generation minimization method.](#) Renewable Energy, 2016.  
24 87: p.1123-1133.
- 25 9. Guo, Q., L. Zhou, and Z. Wang, *Comparison of BEM-CFD and full rotor geometry*  
26 *simulations for the performance and flow field of a marine current turbine.* Renewable  
27 Energy, 2015. **75**: p. 640-648.
- 28 10. Gharali, K. and D.A. Johnson, *Numerical Modeling of an S809 Airfoil under Dynamic Stall,*  
29 *Erosion and High Reduced Frequencies.* Applied Energy, 2012. **93**: p. 45-52.
- 30 11. Zidane, I.F., K.M. Saqr, G. Swadener, X. Ma, and M.F. Shehadeh, *On the role of surface*  
31 *roughness in the aerodynamic performance and energy conversion of horizontal wind turbine*  
32 *blades: a review.* International Journal of Energy Research, 2016. **40**(15): p. 2054-2077.
- 33 12. Iham F. Zidane, G.S., Khalid M. Saqr, Xianghong Ma, Mohamed F. Shehadeh. *CFD*  
34 *Investigation of Transitional Separation Bubble Characteristics on NACA 63415 Airfoil at*  
35 *Low Reynolds Numbers.* in *Proceedings of the 25th UKACM Conference on Computational*  
36 *Mechanics.* 2017. Birmingham, United Kingdom.
- 37 13. Akour, S.N., M. Al-Heydari, T. Ahmed, and K.A. Khalil, *Experimental and theoretical*  
38 *investigation of micro wind turbine for low wind speed regions.* Renewable Energy, 2018.  
39 **116**: p. 215-223.
- 40 14. Darbandi, M., A. Mohajer, A. Behrouzifar, R. Jalali, and G.E. Schneider, *Evaluating the*  
41 *Effect of Blade Surface Roughness in Megawatt Wind Turbine Performance Using Analytical*  
42 *and Numerical Approaches,* in *10th International Conference on Heat Transfer, Fluid*  
43 *Mechanics and Thermodynamics.* 2014: Orlando, Florida.
- 44 15. Pechlivanoglou, G., S. Fuehr, C.N. Nayeri, and C.O. Paschereit, *The Effect of Distributed*  
45 *Roughness on the Power Performance of Wind Turbines,* in *Proceedings of ASME Turbo*  
46 *Expo 2010: Power for Land, Sea and Air GT2010.* 2010: Glasgow, UK.
- 47 16. Chen, X. and R. Agarwal, *Optimization of Flatback Airfoils for Wind Turbine Blades Using a*  
48 *Genetic Algorithm with an Artificial Neural Network,* in *48th AIAA aerospace Sciences*

- 1 Meeting Including the New Horizons Forum and Aerospace Exposition. 2010: Orlando,  
2 Florida.
- 3 17. Ata, R. and Y. Kocyigit, *An Adaptive Neuro-Fuzzy Inference System Approach for Prediction*  
4 *of Tip Speed Ratio in Wind Turbines*. Expert Systems with Applications, 2010. **37**(7): p.  
5 5454-5460.
- 6 18. Yurdusev, M., R. Ata, and N. Cetin, *Assessment of optimum tip speed ratio in wind turbines*  
7 *using artificial neural networks*. Energy, 2006. **31**(12): p. 2153-2161.
- 8 19. Mortazavi, S.M., M.R. Soltani, and H. Motieyan, *A Pareto Optimal Multi-Objective*  
9 *Optimization for a Horizontal Axis Wind Turbine Blade Airfoil Sections Utilizing Exergy*  
10 *Analysis and Neural Networks*. Journal of Wind Engineering and Industrial Aerodynamics,  
11 2015. **136**: p. 62-72.
- 12 20. Saravanan, N. and K.I. Ramachandran, *Incipient Gear Box Fault Diagnosis Using Discrete*  
13 *Wavelet Transform (DWT) for Feature Extraction and Classification using Artificial Neural*  
14 *Network (ANN)*. Expert Systems with Applications, 2010. **37**(6): p. 4168-4181.
- 15 21. Momoh, J.A. and R. Button, *Design and Analysis of Aerospace DC Arcing Faults using Fast*  
16 *Fourier Transformation and Artificial Neural Network in IEEE Power Engineering Society*  
17 *General Meeting 2003: Toronto, Ont., Canada*.
- 18 22. Zhang, Z., *Automatic Fault Prediction of Wind Turbine Main Bearing Based on SCADA Data*  
19 *and Artificial Neural Network*. Open Journal of Applied Sciences, 2018. **08**(06): p. 211-225.
- 20 23. Marten, D., J. Wendler, G. Pechlivanoglou, C.N. Nayeri, and C.O. Paschereit, *Qblade: an*  
21 *Open Source Tool for Design and Simulation of Horizontal and Vertical Axis Wind Turbines*.  
22 *International Journal of Emerging Technology and Advanced Engineering*, 2013. **3**(3): p.  
23 264-269.
- 24 24. Hansen, M., *Aerodynamics of wind turbines* Second ed. 2008, UK: Earthscan.
- 25 25. Bak, C., P. Fuglsang, J. Johansen, and I. Antoniou, *Wind Tunnel Tests of NACA 63-415 and a*  
26 *Modified NACA 63-415 Airfoil, in Risø National Laboratory*. 2000: Roskilde, Denmark.
- 27 26. Lanzafame, R., S. Mauro, and M. Messina, *Wind Turbine CFD Modeling Using a*  
28 *Correlation-Based Transitional Model*. Renewable Energy, 2013. **52**: p. 31-39.
- 29 27. Zidane, I.F., G. Swadener, K.M. Saqr, X. Ma, and M.F. Shehadeh, *CFD Investigation of*  
30 *Transitional Separation Bubble Characteristics on NACA 63415 Airfoil at Low Reynolds*  
31 *Numbers, in Proceedings of the 25th UKACM Conference on Computational Mechanics*.  
32 2017: University of Birmingham, United Kingdom.
- 33 28. Giguere, P. and M.S. Selig, *Low Reynolds Number Airfoils for Small Horizontal Axis Wind*  
34 *Turbines* Wind Engineering, 1997. **21**: p. 367-380.
- 35 29. Zidane, I.F., K.M. Saqr, G. Swadener, X. Ma, and M.F. Shehadeh, *Computational Fluid*  
36 *Dynamics Study of Dusty Air Flow over Naca 63415 Airfoil for Wind Turbine Applications*.  
37 *Jurnal Teknologi*, 2017. **79**(7-3).
- 38 30. T. Mahdaoui, N.B., M. A. Madjoubi, C. Bousbaa, *Study of the Effects of Sand Blasting on*  
39 *Soda Lime Glass Erosion*. INTERNATIONAL REVIEW OF MECHANICAL  
40 ENGINEERING, 2007. **1**: p. 502-510.
- 41 31. Henley, P., *Unpublished soil sample report, Remote Sensing Division, Resewcl Institute, U.S.*  
42 *Army Engineer Topographic Laboratories, Ft Belvoir, VA., 21 Nov 90*.
- 43 32. FLUENT, A., *Theory Guide*. 2011.
- 44 33. Douvi, E.C. and D.P. Margaritis, *Aerodynamic Performance Investigation under the Influence*  
45 *of Heavy Rain of a NACA 0012 Airfoil for Wind Turbine Applications*. International Review  
46 of Mechanical Engineering, 2012. **6**(6): p. 1228-1235.
- 47 34. Morsi, S.A. and A.J. Alexander, *An Investigation of Particle Trajectories in Two Phase Flow*  
48 *Systems*. Journal of Fluid Mechanics, 1972. **55**(2): p. 193- 208.

- 1 35. J. K. Edwards, B.S.M., and S. A. Shirazi, *Evaluation of Alternative Pipe Bend Fittings in*  
2 *Erosive Service*, in *In Proceedings of ASME FEDSM'00: ASME 2000 Fluids Engineering*  
3 *Division Summer Meeting*. 2000: Boston, MA.
- 4 36. Lain, S. and M. Sommerfeld, *Turbulence modulation in dispersed two-phase flow laden with*  
5 *solids from a Lagrangian perspective*. International Journal of Heat and Fluid Flow, 2003.  
6 **24**(4): p. 616-625.
- 7 37. Tsuji, Y., Morikawa, Y., Shiomi, H., *LDV measurements of an air–solid two-phase flow in a*  
8 *vertical pipe*. J. Fluid Mech, 1984. **139**: p. 417–434.
- 9 38. Bose, T., L. Kleiser, and E. Meiberg, Small particles in homogenous turbulence: Settling  
10 velocity enhancement by two-way coupling, Phys. Fluids, 2006. 18: 027102.
- 11 39. Monchoux, R. and A. Dejoan, Settling velocity and preferential concentration of heavy  
12 particles under two-way coupling effects in homogenous turbulence, Phys. Rev. Fluids, 2017.  
13 2: 104302.
- 14 40. Mallouppas, G., W. K. George, and B. G. M. van Wachem, Dissipation and inter-scale  
15 transfer in fully coupled particle and fluid motions in homogeneous isotropic forced  
16 turbulence, Intl. J. Heat Fluid Flow, 2017. 67 (B): 74-85.
- 17 41. Mora, D. O., A. Cartellier, M. Obligado, Experimental estimation of turbulence modification  
18 by internal particles at moderate  $Re_\lambda$ , Phys. Rev. Fluids, 2019. 4: 074309.
- 19 42. Biferale, L., C. Meneveau, R. Vericco, Deformation statistics of sub-Kolmogorov-scale  
20 ellipsoidal neutrally buoyant drops in isotropic turbulence, J. Fluid Mech, 2014. **754**: p. 184–  
21 207.
- 22 43. Spandan, V., D. Lohse, R. Verrico, Deformation and orientation statistics of neutrally  
23 buoyant sub-Kolmogorov ellipsoidal droplets in turbulent Taylor-Couette flow, J. Fluid  
24 Mech, 2016. **809**: p. 480–501.
- 25 44. Montgomerie, B., *Methods for root effects, tip effects and extending the angle of attack range*  
26 *to  $\pm 180^\circ$ , with application to aerodynamics for blades on wind turbines and propellers*. 2004,  
27 Scientific report FOI-R-1305-SE, FOI Swedish defence research agency.
- 28 45. Roffel, B. and B. Betlem, *Process Dynamics and Control*. 2006: John Wiley and Sons, Ltd.
- 29 46. Rumelhart, D.E., G.E. Hinton, and R.J. Williams, *Learning Internal Representations by*  
30 *Error Propagation*. Parallel Distributed Processing, 1986. **1**: p. 318–62.
- 31 47. Hertz, J., A. Krogh, and R.G. Palmer, *Introduction to the Theory of Neural Computation*.  
32 1995, Redwood City: Addison-Wesley Publishing Company.
- 33 48. Goh, A.T.C., *Back-propagation neural networks for modeling complex systems*. Artificial  
34 Intelligence in Engineering, 1995. **9**: p. 143-151.
- 35 49. López, P., R. Velo, and F. Maseda, *Effect of Direction on Wind Speed Estimation in Complex*  
36 *Terrain Using Neural Networks*. Renewable Energy, 2008. **33**(10): p. 2266-2272.
- 37 50. Fadare, D., *The Application of Artificial Neural Networks to Mapping of Wind Speed Profile*  
38 *for Energy Application in Nigeria*. Appl Energy, 2010. **87**: p. 934–42.
- 39 51. Yang, S., W. Li, and C. Wang, *The Intelligent Fault Diagnosis of Wind Turbine Gearbox*  
40 *Based on Artificial Neural Network*. In: Proceedings International Conference on Condition  
41 Monitoring and Diagnosis, 2008: p. 1327–30.
- 42 52. Ata, R., *Artificial Neural Networks Applications in Wind Energy Systems: A Review*.  
43 Renewable and Sustainable Energy Reviews, 2015. **49**: p. 534-562.
- 44 53. Hansen, K.S., K.O.H. Pedersen, and U.S. Paulsen, *Online wind turbine measurement*  
45 *laboratory*, in *EWEC 2006*. 2006: Athens. p. 1-8.
- 46 54. Ju, Y., C. Zhang, and L. Ma, *Artificial Intelligence Metamodel Comparison and Application*  
47 *to Wind Turbine Airfoil Uncertainty Analysis*. Advances in Mechanical Engineering, 2016.  
48 **8**(5): p. 1-14.

49

**Table 1** The equivalent values of the characteristic ratio between the sand and air ( $\alpha$ ) for the three mass flow rate values at Reynolds number 1.6 million.

Mass Flow Rate (kg/s)	Characteristic Ratio Between the Sand and Air ( $\alpha$ )
100	$0.4 \times 10^{-4}$
200	$0.9 \times 10^{-4}$
400	$1.7 \times 10^{-4}$

**Table 2** The equivalent values of the characteristic ratio between the sand and air ( $\alpha$ ) for the three mass flow rate values at Reynolds number 460,000.

Mass Flow Rate (kg/s)	Characteristic Ratio Between the Sand and Air ( $\alpha$ )
100	$1.5 \times 10^{-4}$
200	$3.0 \times 10^{-4}$
400	$5.9 \times 10^{-4}$

**Table 3** The equivalent values of the characteristic ratio between the sand and air ( $\alpha$ ) for the three mass flow rate values at Reynolds number 300,000.

Mass Flow Rate (kg/s)	Characteristic Ratio Between the Sand and Air ( $\alpha$ )
100	$2.3 \times 10^{-4}$
200	$4.5 \times 10^{-4}$

**Table 4** Input and output patterns for CFD and neural network

Pattern Number	Input Data			CFD Output Data	ANN Output Data	ANN Percentage Error – Absolute Value(%)
	Debris Flow Rate(kg/s)	Reynolds Number	AOA	Total Erosion on Chord (g/m <sup>2</sup> )	Total Erosion on Chord (g/m <sup>2</sup> )	
1	100	300000	0	579	613	5.95
2	100	300000	2	654	705	7.79
3	100	300000	4	695	664	4.43
4	100	300000	6	620	710	14.53
5	100	300000	8	1069	993	7.07
6	100	300000	10	1008	1024	1.61
7	200	300000	0	1387	1356	2.19
8	200	300000	2	1266	1139	10.02
9	200	300000	4	1000	983	1.70
10	200	300000	6	1475	1543	4.66
11	200	300000	8	2719	2536	6.72
12	200	300000	10	1944	1945	0.07

13	100	460000	2	790	709	10.25
14	100	460000	4	655	684	4.50
15	100	460000	6	797	694	12.98
16	100	460000	8	855	905	5.91
17	100	460000	10	1140	1021	10.50
18	200	460000	0	1538	1315	14.47
19	200	460000	2	1306	1349	3.28
20	200	460000	4	965	1025	6.18
21	200	460000	6	1321	1211	8.28
22	200	460000	8	1866	2029	8.73
23	200	460000	10	2282	2284	0.08
24	400	460000	0	2457	2455	0.08
25	400	460000	2	1997	2013	0.81
26	400	460000	4	1759	1751	0.45
27	400	460000	6	2255	2061	8.62
28	400	460000	8	2926	2636	9.91
29	400	460000	10	3645	3610	0.97
30	100	1600000	0	770	819	6.40
31	100	1600000	2	575	541	6.01
32	100	1600000	4	389	342	12.00
33	100	1600000	6	655	657	0.34
34	100	1600000	8	832	868	4.31
35	100	1600000	10	832	801	3.75
36	200	1600000	0	1539	1526	0.85
37	200	1600000	2	1151	1001	12.97
38	200	1600000	4	890	891	0.16
39	200	1600000	6	1234	1210	1.98
40	200	1600000	8	1663	1686	1.41
41	200	1600000	10	1554	1501	3.39
42	400	1600000	0	3078	3076	0.05
43	400	1600000	2	2457	2456	0.03
44	400	1600000	4	1554	1621	4.30
45	400	1600000	6	2621	2619	0.07
46	400	1600000	8	3808	3807	0.03
47	400	1600000	10	3107	3102	0.18

Table 5 The Excluded input and output patterns from the neural network training progress

Testing Pattern Number	Input Data			CFD Output Data	ANN Output Data	ANN Percentage Error (%) – Absolute Value
	Debris Flow Rate (kg/s)	Reynolds Number	AOA	Total Erosion on Chord (g/m <sup>2</sup> )	Total Erosion on Chord (g/m <sup>2</sup> )	
4	100	300000	6	620	710.3860241	14.58
8	200	300000	2	1266	1139.177416	10.02
14	100	460000	4	655	684.0733472	4.44
21	200	460000	6	1321	1211.315698	8.30
27	400	460000	6	2255	2060.659089	8.62
32	100	1600000	4	389	341.9535792	12.09
37	200	1600000	2	1151	1001.485368	12.99
44	400	1600000	4	1554	1621.22193	4.33

**Table 6:** The main parameters of Nordtank NTK 500/41

Rotational Speed	27.1 rpm
Rotor Radius	20.5 m
Number of Blades	3
Cut-in Wind Speed	4 m/s
Cut-out Wind Speed	25 m/s
Profile	NACA 63-4xx



## Figure Captions

Figure 1. shows the layout of the wind turbine blade and the airfoil used

Figure 2. Validation of lift ( $C_l$ ) and drag ( $C_d$ ) coefficients for the current study: (a) lift coefficient for NACA 63415 at Reynolds Number  $1.6 \times 10^6$  (b) drag coefficient at Reynolds Number for NACA 63415  $1.6 \times 10^6$  (c) lift coefficient for NACA 63415 at Reynolds Number  $460 \times 10^3$  (d) drag coefficient for NACA 63415 at Reynolds Number  $460 \times 10^3$  (e) lift coefficient for NACA 63415 at Reynolds Number  $300 \times 10^3$  (f) drag coefficient for NACA 63415 at Reynolds Number  $300 \times 10^3$ . Experimental results from Bak et al. [25] all for  $Re = 1.6 \times 10^6$  and shown in all graphs for comparison.

Figure 3. Velocities and forces related to the wind turbine blade

Figure 4. (a) Implemented Neural Network in MATLAB software (b) The neural network outputs with respect to targets (the correct CFD output for each of the input data) for training, validation, and test sets

Figure 5. lift ( $C_l$ ) and drag ( $C_d$ ) coefficients Variation with angle of attacks in clean and sandy conditions. (a) lift coefficient at Reynolds Number  $1.6 \times 10^6$  (b) lift coefficient at Reynolds Number  $460 \times 10^3$  (c) lift coefficient at Reynolds Number  $300 \times 10^3$  (d) drag coefficient at Reynolds Number  $1.6 \times 10^6$  (e) drag coefficient at Reynolds Number  $460 \times 10^3$  (f) drag

Figure 6. Particle traces colored by particle velocity magnitude at angle of attack  $2^\circ$  and  $10^\circ$  (a) Reynolds number  $1.6 \times 10^6$  (b) Reynolds number  $460 \times 10^3$  (c) Reynolds number  $300 \times 10^3$

Figure 7. Suction side erosion (a) Erosion at Reynolds number  $1.6 \times 10^6$  and AOA  $2^\circ$  (b) Erosion at Reynolds number  $1.6 \times 10^6$  and AOA  $10^\circ$  (c) Erosion at Reynolds number  $460 \times 10^3$  and AOA  $2^\circ$  (d) Erosion at Reynolds number  $460 \times 10^3$  and AOA  $10^\circ$  (e) Erosion at Reynolds number  $300 \times 10^3$  and AOA  $2^\circ$  (f) Erosion at Reynolds number  $300 \times 10^3$  and AOA  $10^\circ$ . Only selected regions are shown for clarity. For locations not shown within the range in any figure, the erosion is zero.

Figure 8. Pressure side erosion rate for 3-months period annually at Reynolds number of  $1.6 \times 10^6$  and AOA of  $2^\circ$  for NACA 63415

Figure 9. Pressure side erosion rate for 3-months period annually at Reynolds number of  $1.6 \times 10^6$  and AOA of  $10^\circ$  for NACA 63415

Figure 10. Pressure side erosion rate for 3-months period annually at Reynolds number of  $460 \times 10^3$  and AOA of  $2^\circ$  for NACA 63415

Figure 11. Pressure side erosion rate for 3-months period annually at Reynolds number of  $460 \times 10^3$  and AOA of  $10^\circ$  for NACA 63415 (a) Chord range ( $x/c$ ) from 0 to 0.5 (a) Chord range ( $x/c$ ) from 0 to 0.5

Figure 12. Pressure side erosion rate for 3-months period annually at Reynolds number of  $300 \times 10^3$  and AOA of  $2^\circ$  for NACA 63415

Figure 13. Pressure side erosion rate for 3-months period annually at Reynolds number of  $300 \times 10^3$  and AOA of  $10^\circ$  for NACA 63415 (a) Chord range (x/c) from 0 to 0.5 (a) Chord range (x/c) from 0 to 0.5

Figure 14. (a) Power Coefficient Vs TSR using BEM Model in clean and sandy conditions (b) Torque Coefficient Vs TSR using BEM Model in clean and sandy conditions (c) Power Output using BEM Model in clean and sandy conditions (d) Nordtank NTK 500/41 power curve at different wind speeds in clean and rough conditions

Figure 15. (a) Comparison between the CFD and neural network output values for the total erosion on chord per unit area (b) The absolute percentage error between the CFD and neural network output values for the total erosion on chord per unit area for each pattern used in the reliability test (c) The absolute percentage error between the CFD and neural network output values for the total erosion on chord per unit area for the whole patterns used in neural network training process and reliability test.